

## Quassel IRC - Bug #68

### Introduce class Nick : public QString

01/09/2008 12:51 AM - Sputnik

<b>Status:</b>	Resolved	<b>Start date:</b>	
<b>Priority:</b>	High	<b>Due date:</b>	
<b>Assignee:</b>	Sputnick	<b>% Done:</b>	0%
<b>Category:</b>	General / Unspecified	<b>Estimated time:</b>	0.00 hour
<b>Target version:</b>		<b>OS:</b>	Any
<b>Version:</b>	0.13.1		
<b>Description</b>			
<p>We should introduce a new class containing nick names, including an overloaded compare function. This should make the whole case-insensitivity stuff a heck of a lot easier, and such Nicks should then also be usable as QHash indices without further ado...</p> <p>We should remember the following from RFC 1459:</p> <p>Because of IRC's scandinavian origin, the characters {} are considered to be the lower case equivalents of the characters [], respectively. This is a critical issue when determining the equivalence of two nicknames.</p>			

### History

#### #1 - 01/09/2008 01:17 AM - Sputnik

Update: As usual, the RFC as quoted above has nothing to with the real world. At least on Freenode, {Sput} and [Sput] can gladly coexist...

#### #2 - 10/19/2008 10:23 PM - Sputnik

I think we don't really need this anymore. Might well be cleaner than the current approach, but we shouldn't beat a dead horse here...