

## Quassel IRC - Bug #831

### assert if you "/query" in the input field

10/20/2009 08:51 PM - m4v

<b>Status:</b>	Resolved	<b>Start date:</b>	10/20/2009
<b>Priority:</b>	Normal	<b>Due date:</b>	
<b>Assignee:</b>	johu	<b>% Done:</b>	100%
<b>Category:</b>		<b>Estimated time:</b>	0.00 hour
<b>Target version:</b>	0.6.2	<b>OS:</b>	Any
<b>Version:</b>	0.5.0		

**Description**

just write "/query" and enter.

I tested this while connected to freenode and in some channels.

---

```
% quassel --version
15:49)
Qt: 4.5.2
KDE: 4.3.2 (KDE 4.3.2)
Quassel IRC: v0.5.0 (dist-638987e)
```

(10-20)

```
% lsb_release a
No LSB modules are available.
Distributor ID: Ubuntu
Description: Ubuntu karmic (development branch)
Release: 9.10
Codename: karmic
-
backtrace:

unhandled Error in QSqlQuery!
last Query:
INSERT INTO buffer (userid, networkid, buffername, buffercname, buffertype)
VALUES (:userid, :networkid, :busername, :buffercname, :buffertype)
executed Query:
INSERT INTO buffer (userid, networkid, buffername, buffercname, buffertype)
VALUES (?, ?, ?, ?, ?)
bound Values: :buffercname=NULL, :buffercname=NULL, :buffertype=4, :networkid=1, :userid=1
Error Number: 19
Error Message: constraint failed No es posible obtener la fila
Driver Message: No es posible obtener la fila
DB Message: constraint failed
ASSERT: "bufferId.isValid()" in file /build/buildd/quassel-0.5.0/src/uisupport/bufferviewfilter.cpp, line 303
Quassel IRC: "0.5.0" "638987ec78dde3979a8636d1f131eb1d0d5a9073"
```

Program received signal SIGABRT, Aborted.

```
0x00a74422 in _kernel_vsyscall ()
(gdb) bt
#0 0x00a74422 in __kernel_vsyscall ()
#1 0x01d174d1 in _GI_raise (sig=6) at ../nptl/sysdeps/unix/sysv/linux/raise.c:64
#2 0x01d1a932 in *__GI_abort () at abort.c:92
#3 0x007e5f8c in qt_message_output(QtMsgType, char const) () from /usr/lib/libQtCore.so.4
#4 0x007e606e in qFatal(char const*, ...) () from /usr/lib/libQtCore.so.4
#5 0x007e6165 in qt_assert(char const*, char const*, int) () from /usr/lib/libQtCore.so.4
#6 0x0812f3ac in BufferViewFilter::filterAcceptBuffer (this=0x869d4c8, source_bufferIndex=...) at
/build/buildd/quassel-0.5.0/src/uisupport/bufferviewfilter.cpp:303
#7 0x0812f768 in BufferViewFilter::filterAcceptsRow (this=0x869d4c8, source_row=6, source_parent=...) at
/build/buildd/quassel-0.5.0/src/uisupport/bufferviewfilter.cpp:371
#8 0x011754e3 in ?? () from /usr/lib/libQtGui.so.4
#9 0x0117572f in ?? () from /usr/lib/libQtGui.so.4
#10 0x01176def in QSortFilterProxyModel::qt_metacall(QMetaObject::Call, int, void**) () from /usr/lib/libQtGui.so.4
```

#11 0x0815745f in BufferViewFilter::qt\_metacall (this=0x869d4c8, \_c=QMetaObject::InvokeMetaMethod, \_id=32, \_a=0xbfffe550) at /build/builddd/quassel-0.5.0/obj-i486-linux-gnu/src/uisupport/moc\_bufferviewfilter.cxx:78

#12 0x008f5263 in QMetaObject::activate(QObject\*, int, int, void\*\*) () from /usr/lib/libQtCore.so.4

#13 0x008f5ec2 in QMetaObject::activate(QObject\*, QMetaObject const\*, int, void\*\*) () from /usr/lib/libQtCore.so.4

#14 0x0092e98f in QAbstractItemModel::rowsInserted(QModelIndex const&, int, int) () from /usr/lib/libQtCore.so.4

#15 0x008da460 in QAbstractItemModel::endInsertRows() () from /usr/lib/libQtCore.so.4

#16 0x01174e93 in ?? () from /usr/lib/libQtGui.so.4

#17 0x011754a0 in ?? () from /usr/lib/libQtGui.so.4

#18 0x0117572f in ?? () from /usr/lib/libQtGui.so.4

#19 0x01176def in QSortFilterProxyModel::qt\_metacall(QMetaObject::Call, int, void\*\*) () from /usr/lib/libQtGui.so.4

#20 0x0818680f in BufferModel::qt\_metacall (this=0x839f548, \_c=QMetaObject::InvokeMetaMethod, \_id=32, \_a=0xbfffe8c0) at /build/builddd/quassel-0.5.0/obj-i486-linux-gnu/src/client/moc\_buffermodel.cxx:76

#21 0x008f5263 in QMetaObject::activate(QObject\*, int, int, void\*\*) () from /usr/lib/libQtCore.so.4

#22 0x008f5ec2 in QMetaObject::activate(QObject\*, QMetaObject const\*, int, void\*\*) () from /usr/lib/libQtCore.so.4

#23 0x0092e98f in QAbstractItemModel::rowsInserted(QModelIndex const&, int, int) () from /usr/lib/libQtCore.so.4

#24 0x008da460 in QAbstractItemModel::endInsertRows() () from /usr/lib/libQtCore.so.4

#25 0x081846c0 in TreeModel::endAppendChilds (this=0x839f3d8) at /build/builddd/quassel-0.5.0/src/client/treemodel.cpp:489

#26 0x0818b303 in TreeModel::qt\_metacall (this=0x839f3d8, \_c=QMetaObject::InvokeMetaMethod, \_id=23, \_a=0xbfffeaac) at /build/builddd/quassel-0.5.0/obj-i486-linux-gnu/src/client/moc\_treemodel.cxx:274

#27 0x08189e6f in NetworkModel::qt\_metacall (this=0x839f3d8, \_c=QMetaObject::InvokeMetaMethod, \_id=23, \_a=0xbfffeaac) at /build/builddd/quassel-0.5.0/obj-i486-linux-gnu/src/client/moc\_networkmodel.cxx:613

#28 0x008f5263 in QMetaObject::activate(QObject\*, int, int, void\*\*) () from /usr/lib/libQtCore.so.4

#29 0x008f5ec2 in QMetaObject::activate(QObject\*, QMetaObject const\*, int, void\*\*) () from /usr/lib/libQtCore.so.4

#30 0x0818b4d9 in AbstractTreeItem::endAppendChilds (this=0x843c250) at /build/builddd/quassel-0.5.0/obj-i486-linux-gnu/src/client/moc\_treemodel.cxx:104

#31 0x081853b4 in AbstractTreeItem::newChild (this=0x843c250, item=0x8752828) at /build/builddd/quassel-0.5.0/src/client/treemodel.cpp:51

#32 0x0817e6ca in NetworkItem::bufferItem (this=0x843c250, bufferInfo=...) at /build/builddd/quassel-0.5.0/src/client/networkmodel.cpp:108

#33 0x0817eab4 in NetworkModel::updateBufferActivity (this=0x839f3d8, msg=...) at /build/builddd/quassel-0.5.0/src/client/networkmodel.cpp:1052

#34 0x08087a1a in QtUiMessageProcessor::process (this=0x83a19a0, msg=...) at /build/builddd/quassel-0.5.0/src/qtui/qtuimessageprocessor.cpp:59

#35 0x08164bba in Client::recvMessage (this=0x83b44c8, msg=...) at /build/builddd/quassel-0.5.0/src/client/client.cpp:466

#36 0x081873b9 in Client::qt\_metacall (this=0x83b44c8, \_c=QMetaObject::InvokeMetaMethod, \_id=25, \_a=0xbfffd18) at /build/builddd/quassel-0.5.0/obj-i486-linux-gnu/src/client/moc\_client.cxx:152

#37 0x08213c26 in SignalProxy::invokeSlot (this=0x83cb728, receiver=0x83b44c8, methodId=25, params=..., returnValue=...) at /build/builddd/quassel-0.5.0/src/common/signalproxy.cpp:796

#38 0x08213c6b in SignalProxy::invokeSlot (this=0x83cb728, receiver=0x83b44c8, methodId=25, params=...) at /build/builddd/quassel-0.5.0/src/common/signalproxy.cpp:807

#39 0x08213e18 in SignalProxy::handleSignal (this=0x83cb728, data=...) at /build/builddd/quassel-0.5.0/src/common/signalproxy.cpp:750

#40 0x08214e6a in SignalProxy::receivePeerSignal (this=0x83cb728, sender=0x844e4b8, requestType=@0x852dd08, params=...) at /build/builddd/quassel-0.5.0/src/common/signalproxy.cpp:587

#41 0x08214ecc in SignalProxy::receivePeerSignal (this=0x83cb728, sender=0x839a608, requestType=@0x852dd08, params=...) at /build/builddd/quassel-0.5.0/src/common/signalproxy.cpp:622

#42 0x082162b5 in SignalProxy::customEvent (this=0x83cb728, event=0x852dcf8) at /build/builddd/quassel-0.5.0/src/common/signalproxy.cpp:982

#43 0x008ef65f in QObject::event(QEvent\*) () from /usr/lib/libQtCore.so.4

#44 0x00b95f54 in QApplicationPrivate::notify\_helper(QObject\*, QEvent\*) () from /usr/lib/libQtGui.so.4

#45 0x00b9d67c in QApplication::notify(QObject\*, QEvent\*) () from /usr/lib/libQtGui.so.4

#46 0x06fe1bfa in KApplication::notify(QObject\*, QEvent\*) () from /usr/lib/libkdeui.so.5

#47 0x008df6cb in QCoreApplication::notifyInternal(QObject\*, QEvent\*) () from /usr/lib/libQtCore.so.4

#48 0x008e02b2 in QCoreApplicationPrivate::sendPostedEvents(QObject\*, int, QThreadData\*) () from /usr/lib/libQtCore.so.4

#49 0x008e047d in QCoreApplication::sendPostedEvents(QObject\*, int) () from /usr/lib/libQtCore.so.4

#50 0x0090a3ff in ?? () from /usr/lib/libQtCore.so.4

#51 0x02527e78 in g\_main\_context\_dispatch () from /lib/libglib-2.0.so.0

#52 0x0252b720 in ?? () from /lib/libglib-2.0.so.0

#53 0x0252b853 in g\_main\_context\_iteration () from /lib/libglib-2.0.so.0

#54 0x0090a02c in QEventDispatcherGlib::processEvents(QFlags<QEventLoop::ProcessEventsFlag>) () from /usr/lib/libQtCore.so.4

#55 0x00c36be5 in ?? () from /usr/lib/libQtGui.so.4

#56 0x008ddc79 in QEventLoop::processEvents(QFlags<QEventLoop::ProcessEventsFlag>) () from /usr/lib/libQtCore.so.4

#57 0x008de0ca in QEventLoop::exec(QFlags<QEventLoop::ProcessEventsFlag>) () from /usr/lib/libQtCore.so.4

#58 0x008e053f in QCoreApplication::exec() () from /usr/lib/libQtCore.so.4

#59 0x00b95dd7 in QApplication::exec() () from /usr/lib/libQtGui.so.4

#60 0x0807643d in main (argc=No se puede acceder a la memoria en la dirección 0x6) at /build/builddd/quassel-0.5.0/src/common/main.cpp:139

---

## Associated revisions

---

### Revision 9df2a35dba2c0cb4ca8c28989b9cf776d8e2fdf8 - 05/01/2010 06:58 PM - johu

check empty args for cmds join+query, fixes #831

### Revision 9df2a35d - 05/01/2010 06:58 PM - johu

check empty args for cmds join+query, fixes #831

### Revision f47c3bdeacbc163f558751bf090d499fd1a36cb6 - 05/01/2010 06:59 PM - seezer

Handle /query and /join without args nicely

Adapts MR84 to the refactored ClientUserInputHandler  
Thanks johu for the initial fix!

Fixes #831 and renders MR84 obsolete.

### Revision f47c3bde - 05/01/2010 06:59 PM - seezer

Handle /query and /join without args nicely

Adapts MR84 to the refactored ClientUserInputHandler  
Thanks johu for the initial fix!

Fixes #831 and renders MR84 obsolete.

## History

---

### #1 - 03/11/2010 07:17 PM - johu

- Status changed from *New* to *Confirmed*
- Assignee set to *johu*
- Target version set to *0.6.0*
- OS changed from *Linux* to *Any*

### #2 - 04/23/2010 02:32 AM - johu

- Target version deleted (*0.6.0*)

### #3 - 04/23/2010 10:58 PM - johu

- Target version set to *0.6.2*
- % Done changed from *0* to *90*

### #4 - 05/01/2010 08:44 PM - seezer

- Status changed from *Confirmed* to *Resolved*
- % Done changed from *90* to *100*

Applied in changeset [f47c3bdeacbc163f558751bf090d499fd1a36cb6](#).